ALI-NS1124VR
AC-VS-NS1124VR

WITNESS SERIES

STARLIGHT TECHNOLOGY

CLOUD-ENABLED

4.0 Megapixel IP

4MP STARLIGHT 30′ IR VANDALPROOF WDR WEDGE DOME IP SECURITY CAMERA

Wide angle lens offers a 109° field of view to cover large areas

Monitor and protect your home or business with the Alibi 4.0 Megapixel 30′ IR Vandalproof WDR Outdoor Wedge Dome IP Security Camera.

The network IP camera features a 2.8 mm fixed lens with 109° field of view, along with a 1/2.5″ CMOS progressive-scan image sensor that delivers up to 4.0 megapixel resolution at 30 frames per second (fps).

The 4.0 megapixel IP security camera features integrated IR LEDs that enable the camera to see up to 30′ in the dark. The camera features Smart IR, an Advanced Infrared Technology, which reduces over-exposure of the IR LED at the center of the image without washing out the subject at close range.

The megapixel IP camera is equipped with true day/night (ICR) which captures sharp, detailed color images during the day and black and white images in low light. 120db true wide dynamic range (WDR) and 3D digital noise reduction (3D-DNR) produce exceptional image quality with less noise in variable and low light conditions.

The IP dome camera features a true 3-axis gimbal that simplifies installation, and provides flexible mounting and camera positioning. The tri-axis gimbal enables you to mount the dome camera virtually anywhere (wall or ceiling), and position it at any angle to achieve the desired field-of-view.

The camera's IP66 weather-rated enclosure provides protection from particles such as dust and sand, as well as harsh weather conditions, including rain and snow. The vandal-resistant camera's enclosure is also IK08 impact resistant, which provides protection against physical impact.

The megapixel IP dome camera supports up to 128GB micro SD cards (sold separately). The camera can be powered via 802.3af PoE or 12 Vdc power supply, and is ONVIF Profile S compliant for greater device compatibility and ONVIF Profile G approved.

This camera also features an event log, and event notification, along with email notification.

The free Alibi Witness mobile app enables you to view your live and recorded video remotely—from anywhere, from your Android or iOS mobile device.

What's Included:

+ (1) Alibi 4.0 megapixel 30′ IR vandal-resistant outdoor wedge dome IP security camera
+ (1) Mounting template
+ (1) Set of mounting hardware
+ (1) Quickstart guide

Net Solutions & Security

855-523-5805

https://www.nss1.org

4MP STARLIGHT 30′ IR VANDALPROOF WDR WEDGE DOME IP SECURITY CAMERA

ALI-NS1124VR

SPECIFICATIONS

Imager Type	Progressive Scan CMOS
Imager Size (in)	1/2.5
Color	Yes
Camera Resolution (px)	2688 × 1520 @ 30fps
Megapixel	4.0
Day/Night Function	True D/N w/Mechanical Cut Filter
Digital Noise Reduction (DNR)	3D DNR
Dynamic Range (dB)	120
Electronic Shutter	1/3 - 1/10,000 sec
Flip	Digital Horizontal/Vertical
IR Array Range (ft)	30
IR Wavelength (nm)	850
Lux (B/W)	0.0 (IR ON)
Lux (Color)	0.008
AGC Control	Selectable
Wide Dynamic	Yes
Relative Aperture (F-stop)	F1.6
FOV (degrees)	109
Focus	Fixed
IR Corrective	Yes
Lens Iris	Manual
Lens Mount	M12
Lens Type	Fixed
Focal Length (mm)	2.8
Audio	Yes
Audio Compression	G.711/G.722.1/G.726/MP2L2
Audio Streaming	Two-Way
Built in Mic	Yes
Ethernet Interface	RJ-45
Ethernet Ports	1
Ethernet Speed	10M / 100M self-adaptive
Remote Configuration	Yes
Remote Viewable	Yes
Bit Rate	32 Kbps - 16 Mbps
Compression Type	H.265+, H.265, H.264, H.264+
Email Notification	Yes
Event Log	Yes
Event Notification	Yes
Selectable Frame Rate	Yes
Privacy Video Block	Yes

SD Card Reader	Yes
Storage Capacity (GB)	Up to 128 (micro SD card not included)
Video Analytics Capable	Yes
Video Offload	MP4
Video Streaming	Dual
Dimensions	4.33″ x 2.22″
Pan Angle	-30° - 30°
Tilt Angle	0° - 75°
Card Reader Type	Micro SD card, SDHC, SDXC
Certification	CE, FCC, RoHS
Construction	Polycarbonate (Bubble) / Plastic (Dome cover)
Operating Humidity	0% - 95% (non-condensing)
Operating Temperature (F)	-22° - 140°
Product Color	White
Outdoor	Yes
Ingress Protection	IP66
Vandal-proof	IK08
Weight (lb)	0.88
PoE	802.3af
Power (w)	12 VDC ± 25%
Volts DC	12
Browser Support	Internet Explorer, Apple Safari
Mobile App	iOS & Android
Sensor Inputs	1
Alarm Output	Yes
Alarm Outputs	1
Audio In	2
Audio Out	1
Digital Outputs	1

Net Solutions & Security

855-523-5805

https://www.nss1.org

SPECIFICATIONS

Compatible with:

ALI-AA1
Outdoor Pole Mount Adapter for ALI-AB1 and ALI-AB2 Brackets

ALI-AB2
Long Wall Mount Bracket

ALI-AA2
Outdoor Corner Mount Adapter

ALI-AF7
Wedge Flange Adapter

ALI-AB1
Short Wall Mount Bracket

ALI-AJ13
Round Junction Box