



Key Features:

- + Produces up to 2.0 MP high resolution sensor, 1920 × 1080 @ 60 fps
- + 8 - 32 mm motorized varifocal lens
- + Smart IR LED array with illumination up to 165 feet
- + 3D-DNR noise reduction, 120dB Wide Dynamic Range (WDR)
- + Dual power capable - Power over Ethernet (PoE) or 12 Vdc
- + Weatherproof - IP67 rated
- + Internal microSD card storage up to 128GB (card not provided)
- + 2-way Audio I/O, Alarm I/O

IP 2.0 Megapixel

2MP 165' IR IP LICENSE PLATE RECOGNITION BULLET CAMERA

Features Advanced Infrared Technology for enhanced low light performance

The Alibi 2.0 Megapixel 165' IR IP License Plate Recognition Bullet Security Camera uses high-resolution optical character recognition on images to read vehicle license plates. This camera features a 1/1.8" CMOS progressive-scan image sensor that delivers up to 2.0 megapixel resolution at 60 frames per second (fps) and includes an 8 - 32 mm varifocal lens, which can be used for surveillance of both gate entrances and roadways.

The 2.0 megapixel IP security camera features a single integrated IR LED that enables the camera to see up to 165' in the dark. The camera features Advanced Infrared Technology, which includes Smart IR and Full Frame Illumination.

Smart IR reduces over-exposure of the IR LED at the center of the image without washing out the subject at close range. Black glass on the lens hides the IR LED from view when the IR is not turned on.

Full Frame Illumination, delivers a wider illumination spread and offers several advantages over standard IR technology, including:

- + Produces clearer, brighter images in low light and at night
- + Delivers a wider illumination spread
- + Unique rectangular IR LED design produces a uniformly illuminated image across the entire screen
- + Reduces overexposure at the center of the image and eliminates hot spots
- + Eliminates blooming from lights by reducing ambient light pollution
- + Reduces video noise for a clearer nighttime image, along with reducing bandwidth consumption and video storage requirements
- + Delivers 30% greater energy efficiency

What's Included:

- + (1) Alibi 2.0 megapixel 165' IR license plate recognition bullet camera
- + (1) Quick Installation Guide
- + (1) Mounting Hardware and Template
- + (1) Waterproof RJ-45 LAN coupling
- + (1) Junction box
- + (1) Gang box adapter plate
- + (1) Security Wrench



2MP 165' IR IP LICENSE PLATE RECOGNITION BULLET CAMERA

SPECIFICATIONS

Imager Type	Progressive Scan CMOS
Imager Size (in)	1/1.8
Color	Yes
Camera Resolution (px)	1920 × 1080 @ 60 fps
Megapixel	2.0
Day/Night Function	True D/N w/Mechanical Cut Filter
Digital Noise Reduction (DNR)	3D DNR
Dynamic Range (dB)	120
Electronic Shutter	1 - 1/100,000 sec
IR Array Range (ft)	165
IR Sensitive	Yes
IR Wavelength (nm)	850
Lux (B/W)	0.0 (IR ON)
Lux (Color)	0.002
Still Image Capture	Yes
AGC Control	Selectable
Wide Dynamic	D-WDR
Relative Aperture (F-stop)	F1.6
IR Corrective	Yes
Lens Included	Yes
Lens Iris	DC Auto Iris
Lens Type	Varifocal
Focal Length (mm)	8 - 32
Audio Compression	G.711/G.722.1/G.726/MP2L2
Audio Streaming	Two-Way
802.3	802.3at
Ethernet Interface	RJ-45
Ethernet Ports	1
Ethernet Speed	10/100
Protocols	TCP/IP, HTTP, HTTPS, DHCP, UDP, RTP, RTSP and more
Remote Configuration	Yes
Remote Viewable	Yes
Compression Type	H.264, MPEG-4, MJPEG
Email Notification	Yes
Event Log	Yes
Event Notification	Yes
Event Search	Yes
Selectable Frame Rate	Yes
Motion Detection	Yes
Pre/Post Alarm Recording	Yes
Privacy Video Block	Yes

SD Card Reader	Micro SD card (not included) up to 128 GB
Storage Capacity (GB)	micro SD card, SDHC, SDXC (not included) up to 128 GB
Video Analytics Capable	Yes
Video Streaming	Dual
Dimensions	13.72" × 4.5" × 4.4"
Card Reader Type	SD / SDHC / SDXC card slot, up to 128gb
Certification	CE, FCC, RoHS
Construction	Aluminum
Mounting Bracket Included	Yes
Operating Humidity	95% or less (non-condensing)
Operating Temperature (F)	-22°F - 140°F
Product Color	White/Black
Outdoor	Yes
Ingress Protection	IP67
Weight (lb)	4.5
PoE	Yes
Power (w)	12 Vdc ± 10%, 18.1 W; PoE (802.3at, class 4) 24 W
Volts DC	12
Browser Support	Internet Explorer, Apple Safari
Connectors	RJ-45
Sensor Inputs	1
Alarm Output	Yes
Alarm Outputs	1
Audio In	1
Audio Out	1
Outputs	1Vp-p composite output (75 Ω / BNC)

COMPATIBLE WITH:



Mini Junction Box