



ALIBI®

High Definition Surveillance

ALI-NS1114R



IP

4.0 Megapixel

4.0 MEGAPIXEL 100' IR VARIFOCAL IP TURRET SECURITY CAMERA

Full Frame Illumination technology for clearer, brighter images in any lighting conditions

ALI-NS1114R is a motorized varifocal IP turret camera with 4 megapixel resolution that captures crystal clear video images in any lighting conditions. It features Full Frame Illumination technology, which offers better low-light and nighttime surveillance capabilities than standard infrared (IR), and reduces bandwidth consumption and video storage requirements. With H.265+ video compression technology, this IP turret camera uses less hard drive space to store video footage, and enables faster, more fluid remote viewing.

- + **High Resolution Video** - 4 megapixel camera captures smooth video with a high level of clarity and detail
- + **Powerful Night Vision** - Full Frame Illumination technology enables clear nighttime video by eliminating hotspots and blooming from ambient light sources
- + **Adjustable Field of View** - Motorized varifocal lens enables adjustment of the camera's field of view from 92.8° to 29°, for maximum flexibility and ease of installation
- + **H.265+ Compression** - Store more information utilizing less hard drive space, view more channels remotely, and enjoy more fluid remote viewing
- + **Superior Outdoor Performance** - With an IP67 weather-rated metal enclosure, this turret camera has an operating temperature rating of -22° to 140°F and is protected from elements such as dust, rain and sand

What's Included:

- + Mounting Template
- + Mounting Hardware
- + Quick Start Guide





SPECIFICATIONS

Imager Type	Progressive Scan CMOS
Imager Size (in)	1/3
Color	Yes
Camera Resolution (px)	2560 × 1440 @ 20fps
Megapixel	4.0
Day/Night Function	True D/N w/Mechanical Cut Filter
Digital Noise Reduction (DNR)	3D DNR
Dynamic Range (dB)	120
Electronic Shutter	1/3s - 1/100,000s
Flip	Digital Horizontal/Vertical
IR Array Range (ft)	100
IR Wavelength (nm)	850
Lux (B/W)	0.0
Lux (Color)	0.01
AGC Control	Selectable
Wide Dynamic	Yes
Relative Aperture (F-stop)	F1.6
IR Corrective	Yes
Lens Iris	Fixed
Lens Type	Varifocal
Focal Length (mm)	2.8 - 12
Ethernet Interface	RJ-45
Ethernet Ports	1
Ethernet Speed	10M / 100M self-adaptive
Protocols	TCP/IP, HTTP, HTTPS, DHCP, UDP, RTP, RTSP and more
Remote Configuration	Yes
Remote Viewable	Yes
Bit Rate	32Kbps - 8Mbps
Compression Type	H.265+, H.265, H.264, H.264+
Email Notification	Yes
Event Log	Yes
Event Notification	Yes
Selectable Frame Rate	Yes
Privacy Video Block	Yes
SD Card Reader	Yes
Storage Capacity (GB)	Up to 128 (micro SD card not included)
Video Analytics Capable	Yes
Video Streaming	Dual
Dimensions	5.1" x 4.6"

Pan Angle	0°-355°
Tilt Angle	0° - 75°
Rotate Angle	0°-360°
Card Reader Type	Micro SD card, SDHC, SDXC
Certification	CE, FCC, RoHS
Construction	Plastic and Metal Alloy
Operating Humidity	0% - 95% (non-condensing)
Operating Temperature (F)	-22° - 140°
Product Color	White
Outdoor	Yes
Ingress Protection	IP67
Weight (lb)	1.2
PoE	802.3af
Power (w)	12 VDC ± 25%, PoE (802.3af, class 3)
Mobile App	iOS & Android

COMPATIBLE WITH:



ALI-AA1
Outdoor Pole Mount Adapter
for
ALI-AB1 and ALI-AB2
Brackets



ALI-AB2
Long Wall Mount Bracket



ALI-AA2
Outdoor Corner Mount
Adapter



ALI-AB6
Wall Mounting Bracket for
Dome Camera



ALI-AB1
Short Wall Mount Bracket