



IP 4.0 Megapixel

4.0 MEGAPIXEL ILLUMINITE 100' WHITE LIGHT IP BULLET CAMERA

4 megapixel resolution with IllumiNite white light LED technology and Starlight chipset for clear, bright images in any lighting conditions

ALI-NS4114L is a network IP bullet camera with 4 megapixel resolution that features cutting edge technologies to help you capture hi-res, full color video 24/7/365. IllumiNite technology features a white light LED strategically placed below the camera lens that can be set to turn on at a specific time to let you capture color video any time of the night. Combined with the next gen Starlight chipset, you have a powerful camera that lets you capture color video all night long – even in the darkest environments.

What's Included:

- + Mounting Template
- + Mounting Hardware
- + Quick Start Guide

- + **IllumiNite White Light LED** – Powerful white light illuminates the surveillance area to act as a deterrent and to provide enough light to capture full color video, even in the darkest circumstances
- + **High Resolution Video** – 4 megapixel camera captures smooth video with a very high level of clarity and detail
- + **Starlight Chipset** – Super low light LUX rating means this camera can capture color video in extreme low light conditions, even without the LED.
- + **Video Analytics** – Powerful video analytics including line crossing, intrusion detection, face detection and more, to protect people and property more effectively
- + **Superior Outdoor Performance** – With an IP67 weather-rated metal enclosure, this bullet camera has an operating rating of -22° to 140°F and is protected from elements such as dust, sand and rain
- + **Onboard Storage** – Built-in micro SD/SDHC/SDXC slot (card not included), enables local storage up to 128GB





SPECIFICATIONS

Imager Type	Progressive Scan CMOS
Imager Size (in)	1/1.8
Color	Yes
Camera Resolution (px)	2688 x 1520 @ 30 fps
Megapixel	4.0
Day/Night Function	Yes
Digital Noise Reduction (DNR)	3D DNR
Dynamic Range (dB)	120
Electronic Shutter	1/3s - 1/100,000s
LED White Light	3000K
LED Illumination Range	100
Lux (Color)	0.0014 (0.0 with light)
AGC Control	Selectable
Wide Dynamic	Yes
FOV (degrees)	94°
Focus	Fixed
Lens Mount	M14
Focal Length (mm)	4
Audio	Yes
Audio Compression	G.711/G.722.1/G.726/MP2L2
Audio Streaming	One-Way
Built in Mic	Yes
Ethernet Interface	RJ-45
Ethernet Ports	1
Ethernet Speed	10/100
Protocols	TCP/IP, HTTP, HTTPS, DHCP, UDP, RTP, RTSP and more
Remote Configuration	Yes
Remote Viewable	Yes
Bit Rate	32Kbps - 16Mbps
Compression Type	H.265+, H.265, H.264+, H.264, MJPEG
Email Notification	Yes
Event Log	Yes
Event Notification	Yes
Privacy Video Block	Yes
SD Card Reader	Yes
Storage Capacity (GB)	Up to 128 (micro SD card not included)
Video Analytics Capable	Yes
Dimensions	15.2" x 7.5" x 7.1"
Pan Angle	0°-360°

Tilt Angle	0° - 90°
Rotate Angle	0°-360°
Card Reader Type	Micro SD card, SDHC, SDXC
Construction	Plastic and Metal Alloy
Operating Humidity	0% - 95% (non-condensing)
Operating Temperature (F)	-22° - 140°
Product Color	White
Outdoor	Yes
Ingress Protection	IP67
Weight (lb)	2.6
PoE	802.3af
Power (w)	12 VDC, max. 9.5 W PoE: (802.3af), max. 11 W
Volts DC	12
Mobile App	iOS & Android

COMPATIBLE WITH:



ALI-AJ12
Junction Box for
Varifocal Bullet Cameras



ALI-AA2
Outdoor Corner Mount
Adapter



ALI-AJ1
Round Junction Box



ALI-AA1
Outdoor Pole Mount Adapter
for
ALI-AB1 and ALI-AB2
Brackets