



2.0 Megapixel

HD

2MP STARLIGHT HD-TVI/AHD/CVI/CVBS 70' IR OUTDOOR VANDALPROOF DOME CAMERA

2 megapixel resolution, 4 in 1 video output, with wide angle lens and Starlight chipset for clear, bright images in any lighting conditions

ALI-TP1122VR is a wide angle dome camera with 2 megapixel resolution that captures crystal clear video images in any lighting conditions. It features a Starlight chipset and Full Frame Illumination technology, which offers better low-light and nighttime surveillance capabilities than standard infrared (IR), and reduces bandwidth consumption and video storage requirements. With 4 in 1 video output (switchable TVI/AHD/CVI/CVBS), this camera offers the utmost compatibility with existing analog camera systems, making it easy to upgrade your video security system.

What's Included:

- + Mounting Template
- + Mounting Hardware
- + Quick Start Guide

- + **High Resolution Video** - 2 megapixel camera captures smooth video with a very high level of clarity and detail
- + **Wide Angle Lens** - 2.8 mm lens offers a wide 106° field of view
- + **Starlight Chipset** - Super low light LUX rating means this camera can capture color video in extreme low light conditions
- + **Powerful Night Vision** - Full Frame Illumination technology enables clear nighttime video by eliminating hotspots and blooming from ambient light sources
- + **Compatibility with Existing Camera Systems** - 4 in 1 video output (switchable TVI/AHD/CVI/CVBS) offers extreme flexibility when upgrading your analog camera system
- + **Superior Outdoor Performance** - With an IP67 weather-rated metal enclosure, this dome camera has an operating temperature rating of -40° to 140°F and is protected from elements such as dust, sand and rain



SPECIFICATIONS

Imager Type	CMOS
Color	Yes
Camera Resolution (px)	1080p
Megapixel	2.0
Day/Night Function	True D/N w/Mechanical Cut Filter
Digital Noise Reduction (DNR)	3D DNR
Dynamic Range (dB)	120
Electronic Shutter	1/30 - 1/50,000 sec
Effective Pixels	1920(H) × 1080(V)
Lux (B/W)	0.0 (IR ON)
Lux (Color)	0.005
AGC Control	Selectable
Wide Dynamic	Yes
Relative Aperture (F-stop)	F1.2
FOV (degrees)	106°
Lens Mount	M12
Lens Type	Fixed
Focal Length (mm)	2.8
Dimensions	4.4" × 3.2"
Pan Angle	0° to 355°
Tilt Angle	0° - 75°
Rotate Angle	0° to 355°
Construction	Metal
Operating Humidity	0% - 90% (non-condensing)
Operating Temperature (F)	-40° - 140°
Product Color	White
Outdoor	Yes
Ingress Protection	IP67
Vandal-proof	IK10
Weight (lb)	1.1
Power (w)	12 VDC ± 25%; max 4.6W
Outputs	switchable HD-TVI/AHD/CVI/ CVBS

COMPATIBLE WITH:



ALI-AA1
Outdoor Pole Mount Adapter
for ALI-AB1 and ALI-AB2
Brackets



ALI-AB3
Ceiling Pendant Mount
Bracket



ALI-AA2
Outdoor Corner Mount
Adapter



ALI-AB5
Wall Mount Bracket for
Domes




ALI-AB1
Short Wall Mount Bracket



Flange Adapter
ALI-AF4



ALI-AB2
Long Wall Mount Bracket



ALI-AJ4
Round Junction Box